



BSC09 and BS09 is a widely used Access Control in the office. Choosing a lot of stable original parts, strictly follow the national security product standard .BSC09 and BS09 is suitable for the entrances and exits of office, factory, hotel, school, etc. All input /output are using anti-jamming protection and over-voltage/circuit protection. The product experiences the strict degradation test before leaving factory. The greatest advantage of BSC09 and BS09 is easy to install, with multifunctional and elegant design .

TECHNICAL PARAMETERS

Fingerprint Capacity	3000 templates
Transaction Capacity	100,000
Hardware Platform	BIO510
Sensor	Optical Sensor
Algorithm Version	BIO VX10.0
Power Supply	12V DC
Communication	RS232/485,TCP/IP,USB-host
Display	LCD with two lines display
Standard Functions	Work code, Web-server
Wiegand Signal	Input & Output
Operating Temperature	0 °C - 45 °C
Operating Humidity	20% - 80%
Dimension	73x148x34.5mm



BSC09



BS09

OPTIONAL




BSR100


BSR100 is a slave reader which captures the fingerprint image and transfer it to the master terminal for verification



Time zone access control



Perfect combination of fingerprint and card



Multiple communication methods



AB Global SDN. BHD.

51A, 1st Floor, Kalan Kenari 17F, Bandar Puchong Jaya, 47100 Puchong, Selangor Darul Ehsan, Malaysia.

TEL 603-8075 2263 FAX 603-8070 4487 H/P 012-68906301

website www.abglobal.com.my email enquire@abglobal.com.my