




The EBELCO's Drop Bolt locks are renowned with its excellent reliability and the remarkable features.

The series compliance to CE and manufactured under the highest quality control to achieve the commitment to customer who always satisfied with maximum quality and reliability.




SPECIFICATIONS:

- ▶ **Voltage Input** : 12 VDC
- ▶ **Current Draw** : 100mA (Standby) ; 1000mA (Start)
- ▶ **Locking Force** : Up to 800KG
- ▶ **Sensor Monitor Rating** : 0.5Amp,30VAC/VDC max
- ▶ **Gap Sensing Distance** : 8mm
- ▶ **Material** : Solid S/Steel Φ 16mm Bolt
- ▶ **Operating Temperature** : 0~55° C (14~131° F)
- ▶ **Operating Humidity** : 0~90% (non condensing)
- ▶ **Weight (Magnet)** : 0.7 kg
- ▶ **Dimensions** : Face Plate - (L)205x(W)35x(H)40 mm
Strike - (L)90x(W)25x(T)2 mm



FEATURES:

- ▶ **Failed Safe Operation (energized to lock)**
- ▶ **Low Surface Temperature**
- ▶ **Low Power Consumption**
- ▶ **Door Status Output NC & COM**
- ▶ **Reliable Locking Mechanism (MTBF Upto 500,000 Cycles)**
- ▶ **Auto Re-lock Timer 0,3,6,9 sec.**
- ▶ **Durable and Silence Operation**
- ▶ **Carrulous Line Finish Aluminum Surface**
- ▶ **Reverse Current Protection PCB**
- ▶ **Full Range of Optional Brackets**
- ▶ **Standard Packing - 30 units**



Auto Re-Locking
Timer Settings

WIRING INSTRUCTION:-

- RED** - Positive (+)
- BLACK** - NEGATIVE (-)
- WHITE** - NC & COM

Disclaimer :

EBELCO reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication.

SECURITY . QUALITY . RELIABILITY